


BARRIER RAIL REFLECTOR INSTALLATION



TYPICAL GUARDRAIL-GUIDE POST INSTALLATION

## NOTES:

- ALL REFLECTORS SHALL BE SELECTED & INSTALLED PURSUANT TO THE PROJECT PLANS & SPECIFICATIONS OR AT THE DIRECTION OF THE ENGINEER. THE DEPICTED REFLECTORS ARE FOR MOUNTING LOCATION INFORMATION ONLY.
- 2. SPACING: SEE "REFLECTOR PLACEMENT ON GUARDRAIL" NOTES AND TABLE "A", OF THIS SHEET.
- 3. REFLECTORS SHALL BE MOUNTED AT THE ANGLE SPECIFIED BY THE MANUFACTURER OR AS DIRECTED BY THE ENGINEER.
- 4. COLOR: SHALL COMPLY WITH THE GUIDELINES ESTABLISHED BY THE CURRENTLY ADOPTED M.U.T.C.D. EDITION.


## REFLECTOR PLACEMENT SPACING ON GUARDRAIL/BARRIER RAIL:

SPACING SHALL BE:

- (a) 50' ON TANGENTS AND ON CURVES OF 300' RADIUS OR GREATER. IF LESS THAN 300' RADIUS SEE TABLE A.
- (b) REFLECTORS SHALL BE OMITTED ON THE FLARED SECTIONS OF GUARDRAIL.
- (c) NO DIRECT PAYMENT FOR REFLECTORS ON BARRIER RAIL.

## TABLE A

Radius of Curve	Reflector Spacing
	20' 30' 35' 40' 50'



GUARDRAIL-GUIDE POST LOCATION

NEVADA DEPARTMENT OF TRANSPORTATION

REFLECTORS
GUARDRAIL-GUIDE POST

REVISION